

- (54) Title
LOW ALCOHOL WINE PRODUCTION
- (51)⁴ International Patent Classification(s)
C12G 001/00
- (21) Application No. : 47936/85 (22) Application Date : 27.09.84
- (23) Filing Date of Complete Specification : 26.09.85
- (43) Publication Date : 10.04.86
- (44) Publication Date of Accepted Application : 07.09.89
- (60) Related to Provisional(s) : PG7363
- (71) Applicant(s)
BIOQUIP AUSTRALIA PTY. LTD.; COMMONWEALTH SCIENTIFIC AND INDUSTRIAL
RESEARCH ORGANIZATION
- (72) Inventor(s)
DONALD JOHN CASIMIR; TIMOTHY RALSTON LANG
- (74) Attorney or Agent
F.B. RICE & CO.
- (56) Prior Art Documents
42281/85 C12G 003/08
US 4363264 A23N 001/00

(57) Fig. 1 is a flow diagram showing a process for making low alcohol wine according to the present invention, and

Fig. 2 is a longitudinal vertical section through an extractor for carrying out the separation of a sugar containing liquid into a high sugar stream and a low sugar stream according to the present invention.

Claim

1. A method for the production of low alcohol wine comprising separating a fruit juice into a high sugar fraction and a low sugar fraction, stripping volatile components, such as high-boiling point esters, from the fruit juice or from the high sugar fraction and adding them to the low sugar fraction, and fermenting the low sugar fraction.
3. A method as claimed in claim 1 wherein the juice is frozen to form a slush, said slush is passed into an inlet end of an extractor comprising a housing, which is upwardly inclined from its inlet end to an outlet end, and a helical screw conveyor disposed in the housing, rotating the helical

screw conveyor and intermittently changing the direction of rotation of the screw conveyor while maintaining a net forward motion of the solids from the inlet end to the outlet end of the conveyor in a manner such that a solid low sugar containing fraction is discharged from the outlet end of the extractor and a high sugar containing fraction of unfrozen or melted liquid drains from the lower inlet end of the extractor.

COMMONWEALTH OF AUSTRALIA

Patent Act 1952

C O M P L E T E S P E C I F I C A T I O N


(ORIGINAL)

Class

Int. Class

Application Number : PG 7363
Lodged : 27 September 1984


Complete Specification Lodged :
Accepted :
Published :



Priority:

Related Art :

This document contains the amendments made under Section 49 and is correct for printing.



479 36/85

Name of Applicant : BIOQUIP AUSTRALIA PTY. LIMITED and
COMMONWEALTH SCIENTIFIC AND
INDUSTRIAL RESEARCH ORGANIZATION

Address of Applicant : 621 Pacific Highway, Artarmon, New
South Wales, Commonwealth of
Australia and 14 Limestone Avenue,
Campbell, Australian Capital
Territory, Commonwealth of Australia

Actual Inventor : DONALD JOHN CASIMIR & TIMOTHY
RALSTON LANG

Address for Service : F.B. RICE & CO.,
Patent Attorneys,
28A Montague Street,
BALMAIN. 2041.

Complete Specification for the invention entitled:

"LOW ALCOHOL WINE"

The following statement is a full description of this invention including the best method of performing it known to Us:-



The present invention relates to a method for the production of low alcohol wine and to a low alcohol wine so produced.

5 Wine is the fermented juice of fruit, particularly grapes. The natural alcohol content of wine will depend upon the sugar content of the fruit juice. Typically grapes when picked ripe will yield a juice containing about 19% by weight fermentable sugar. Such juice, if fermented to dryness, i.e. to a point where all the sugar is
10 consumed, will have an alcohol content of about 12% by volume. It is possible to stop the fermentation before all the sugar has been fermented however this will necessarily result in a sweet wine. The degree of sweetness in low alcohol wines produced by this method is unacceptable.

15 It is also known to ferment the fruit juice to dryness and then to de-alcoholise the wine by, for instance, vacuum evaporation. This process is both expensive and deleterious to wine quality.

20 In another process as disclosed in U.S. Patent 4,468,407 (Vella), there is provided a method of producing low alcohol wine wherein a standard alcoholic beverage is cooled to produce a liquid fraction which is high in alcohol and a solid fraction that is low in alcohol. The advantage of this process lies in the use of low
25 temperature to separate the fractions thereby ensuring minimal loss of flavour.

30 The present inventors have developed an alternative approach to the production of low alcohol wine by separating the unfermented fruit juice into a high sugar fraction and a low sugar fraction, removing volatile components from the unfermented fruit juice or from the high sugar fraction and transferring them to the low sugar fraction which is then fermented. In this way low alcohol wine may be produced cheaply and the neutral, or
35 deflavoured, high sugar stream is available for other uses.

The present invention consists in a method for the production of low alcohol wine comprising separating a fruit juice into a high sugar fraction and a low sugar fraction, stripping volatile components, such as high-boiling point esters, from the fruit juice or from the high sugar fraction and adding them to the low sugar fraction, and fermenting the low sugar fraction.

The present invention further consists in a low alcohol wine produced by a method according to the present invention.

In another aspect the present invention consists in a process for the separation of a sugar containing liquid into a high sugar fraction and a low sugar fraction, comprising cooling the liquid until at least a part, but preferably not all, of the liquid is frozen and forms particulate solids, passing the so frozen slush into an inlet end of an extractor comprising a housing which is upwardly inclined from its inlet end to an outlet end, and a helical screw conveyor disposed in the housing, rotating the helical screw conveyor and intermittently changing the direction of rotation of the screw conveyor while maintaining a net forward motion of the solids from the inlet end to the outlet end of the conveyor in a manner such that the low sugar containing solids are discharged from the outlet end of the extractor and the high sugar fraction of unfrozen or melted liquid drains from the lower, inlet, end of the extractor.

In a further and more general aspect the present invention comprises separating a solute containing liquid into a high solute fraction and a low solute fraction comprising cooling the liquid until at least a part of the liquid is frozen and forms particulate solids, passing the so frozen liquid into an inlet end of an extractor comprising a housing which is upwardly inclined from its inlet end to an outlet end, and a helical screw conveyor disposed in the housing, rotating the helical screw conveyor

and intermittently changing the direction of rotation while maintaining a net forward motion of the solids from the inlet end to the outlet end of the conveyor and removing any unfrozen or melted liquid from the inlet end of the extractor such that a solid, high solute, fraction is produced at the outlet end of the extractor and a liquid low solute, fraction is produced at the inlet end of the extractor.

While this process is particularly adapted for use with aqueous solutions it could also be used with organic solutions. The process is hereinafter described with reference to sugar solutions but the process could equally well be used with other solutions. As an example the process could be used for concentrating ethanol in aqueous solutions.

In preferred embodiments of the invention the fruit juice will be grape juice however the juice of other fruits could also be similarly treated to produce low alcohol wines. The fruit are preferably crushed, dejuiced and pressed in a conventional manner. The juice may also be clarified and refrigerated if desired, again in a conventional manner.

The juice is separated into a high sugar stream and a low sugar stream. This is most preferably done by freezing the juice to form a slush containing a solid low sugar fraction and a liquid high sugar fraction. The solid low sugar fraction will be separated from the high sugar fraction. It will be appreciated that the separation into high and low sugar fractions could also be carried out by ultrafiltration, reverse osmosis, centrifugation, flotation or rotary vacuum filtration, or by any other suitable technique.

If the juice is to be separated into fractions by freezing to form a slush this is best done in a scraped surface slush freezer although it will be appreciated that other types of freezer could be used. The slush is most

preferably separated into its solid and liquid components in a counter-current diffusion extractor such as is described in U.S. Patent Specification 4,363,264. In this equipment the liquid fraction may be drained from the solid frozen
5 fraction. In addition water, fruit juice or melted low sugar fraction may be run in counter-current with the slush. This will have the effect of carrying the high sugar solution clear of the frozen particles of the low sugar fraction and enhance the separation of the high and low
10 sugar fractions. The absolute concentration of the sugar in the high sugar stream will however be lowered by the use of such a counter-current stream. The use of this apparatus has been found to bring about the efficient separation of the solids from the liquid. The intermittent reversal of
15 direction of the screw conveyor has been found to prevent the icy solids from compacting into a solid block which would be difficult to handle and from which it would be difficult to get the high sugar fraction to drain.

The ratio of the volume of the high sugar fraction to
20 the volume of the low sugar fraction is preferably from 40:60 to 70:30, more preferably from 50:50 to 60:40. The sugar content of the two fractions preferably varies by from 2 to 30% by weight of sugar, more preferably from 10 to 25% by weight. The high sugar fraction will typically contain
25 from 20 to 30% by weight of sugar while the low sugar fraction will typically contain from 5 to 15% by weight of sugar.

The high sugar fraction will contain, in addition to the sugar, a number of volatile components which are
30 typically high boiling point esters. These volatile components give to the finished wine flavours which are characteristic of the fruit and/or of the particular variety of the fruit from which the juice is derived. These esters are stripped from the high sugar fraction and added to the
35 low sugar fraction in appropriate concentration. This

stripping of the boiling point esters may be done in any suitable fractional distillation column however it is preferably done in a spinning cone column such as is described in Australian patent specification 62264/73. In columns of this type radial fins reduce the pressure across the column. This allows high separation efficiencies to be achieved at low distillation temperatures.

The stripped component from the high sugar fraction typically comprises from 1 to 15% by volume of that fraction, preferably 6 to 11% by volume. The remaining neutral high sugar fraction will contain a substantial amount of fruit derived sugar and may be used for fermentation and subsequent distillation to fortifying spirit, for addition to wine for sweetening purposes, or for addition to canning syrups and the like for use in the food industry.

A third component may be added to the low sugar fraction if desired. This third component is derived from the pressed skins of the fruit and may be used to add acid, flavour, tannins and colour to the low sugar fraction. This third component, hereinafter called the skin fraction, is particularly useful in the making of wine from grapes. In this fruit significant flavourants and colourants are largely contained in the grape skins and it is desirable that a proportion of these materials be incorporated into the finished wine.

The skin fraction is formed by extracting the pressed skins, commonly referred to as marc, with water or with low sugar fraction and clarifying the skin fraction if desired. The extraction is preferably carried out in a counter current diffusion extractor substantially as described in U.S. Patent Specification 4,363,264.

In this apparatus the pressed skins of the fruit are conveyed in one direction by the screw conveyor while a counter flowing liquid such as water, the low sugar fraction

or raw grape juice is flowed in the other direction through the housing containing the screw conveyor. If desired the skin fraction is clarified in a conventional manner. If the counter flowing liquid bringing about the extraction is water it may be desirable to concentrate the skin fraction prior to its addition to the low sugar fraction. This concentration may be brought about by evaporation, membrane separation or any other conventional technique.

Hereinafter described by way of example only is a preferred embodiment of the present invention described with reference to the accompanying drawings in which:-

Fig. 1 is a flow diagram showing a process for making low alcohol wine according to the present invention, and

Fig. 2 is a longitudinal vertical section through an extractor for carrying out the separation of a sugar containing liquid into a high sugar stream and a low sugar stream according to the present invention.

Grapes 1 are fed to a crusher 2, a dejuicer 3 and a press 4 for crushing and pressing in a conventional way. The unclarified juice amounted to approximately 820 litres of juice per tonne of grapes crushed and had a sugar content of 19% by weight. The juice was run into a tank 5.

The juice from tank 5 was clarified in a clarifier 7 which comprised a centrifuge, a rotary drum solids filter or a pressure leaf filter and the clarified juice was cooled in refrigerator 8 and passed to cold room 9 for storage at a temperature of about -2°C .

The stored juice is, as required, passed through a plate heat exchanger 12 which receives the cooled juice from cold room 9 and passes it to a scraped surface slush freezer 13.

In the scraped surface slush freezer 13 the juice is partly frozen to form a slush having a solid phase of a relatively dilute sugar content - the low sugar fraction - and a liquid phase of a relatively concentrated sugar content - the high sugar fraction.

The slush so formed is passed to a counter current extractor 10(b) substantially as described with reference to U.S. Patent Specification 4,363,264, except that there is no heating. As is seen in Fig. 2 the counter current diffusion
5 extractor 10 comprises a trough-like housing 31 having an inlet 32 at one end and an outlet 33 at the other. The housing is inclined upwardly from its inlet end 32 to its outlet end 33. A helical screw conveyor 34 is disposed within the housing 31 and is arranged to be rotated about
10 its own longitudinal axis. The conveyor 34 is rotated by a motor 35. A gear box 36 disposed between the motor 35 and conveyor 34 which causes the direction of rotation of the conveyor 34 to be intermittently changed while preserving a net forward motion of any solids in the extractor 10(b)
15 towards the outlet end 33 of the housing 31. A liquids outlet 37 is provided at the lower end of the housing and a liquids inlet 38 is provided at the upper end of the housing to allow the passage of a liquid in counter current with the solids in the extractor 10(b) if required.

20 The solids in the slush from the scraped surface slush freezer 13 are carried upwardly through the extractor 10(b) by the screw conveyor 34. The intermittent reversal of direction of the screw conveyor 34 increases the efficiency with which the high sugar fraction is drained from the
25 solids and removed with the added counterflowing liquid stream or remelt as required. This also prevents compaction of the solids into large frozen blocks.

On discharge from the outlet 33 of the extractor 10(b) the solid low sugar fraction is passed through the heat
30 exchanger 18 to facilitate its melting and then into tank 21. Typically the low sugar fraction was produced in an amount of 320 litres per tonne of grapes pressed and had a sugar content of 10% by weight.

The liquid fraction discharged through liquid outlet 37
35 is the high sugar fraction and comprised typically 480

litres per tonne of grapes pressed and had a sugar content of 28% by weight. This high sugar fraction contains many of the flavourant compounds which give the wine its characteristic flavour. These are stripped in a spinning cone column 20 having 40 cone sets and a 6 inch diameter. Fins are present on the underside of the rotating plates as described in Australian patent specification 62264/73. The operation of the column was adjusted such that about 50 litres of stripped flavourant fraction was removed from the high sugar fraction per tonne of grapes pressed. These flavourants were combined in tank 21 with the low sugar fraction.

The pressed skins 6 from the press 4 were passed to another counter current extractor 10(a) where they were passed in counter current with water 24. The extracted skins 15 which had passed through the outlet 33 of the extractor 10(a) were dumped. The extract skin fraction 11 amounted to 100 litres per tonne of grapes crushed and had a 10% sugar content. The skin fraction 11 was fined, clarified in clarifier 7, refrigerated in refrigerator 8 and stored in cold room 16. This clarified and chilled skin fraction was added to the low sugar fraction in tank 21 yielding a total combined low sugar fraction of 420 litres per tonne of grapes and having about a 10% sugar content by weight.

The low sugar fraction was fermented and clarified in the usual way to yield a low alcohol wine containing 6% alcohol by volume and representing 400 litres per tonne of grapes crushed. If desired this wine, which is dry could be sweetened by the addition of some of the low sugar fraction or juice after fermentation has been completed. This will further reduce the alcohol content of the finished wine to about 5%.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. A method for the production of low alcohol wine comprising separating a fruit juice into a high sugar fraction and a low sugar fraction, stripping volatile components, such as high-boiling point esters, from the fruit juice or from the high sugar fraction and adding them to the low sugar fraction, and fermenting the low sugar fraction.
2. A method as claimed in claim 1 wherein the juice is frozen to form a slush, and said slush is filtered to yield a solid low sugar fraction and a liquid high sugar fraction.
3. A method as claimed in claim 1 wherein the juice is frozen to form a slush, said slush is passed into an inlet end of an extractor comprising a housing, which is upwardly inclined from its inlet end to an outlet end, and a helical screw conveyor disposed in the housing, rotating the helical screw conveyor and intermittently changing the direction of rotation of the screw conveyor while maintaining a net forward motion of the solids from the inlet end to the outlet end of the conveyor in a manner such that a solid low sugar containing fraction is discharged from the outlet end of the extractor and a high sugar containing fraction of unfrozen or melted liquid drains from the lower inlet end of the extractor.
4. A method as claimed in claim 3 wherein water, fruit juice or melted low sugar fraction is run in counter-current with the slush.
5. A method as claimed in any one of claims 1 to 4 wherein the ratio of the volume of the high sugar fraction to the volume of the low sugar fraction is from 40:60 to 70:30.
6. A method as claimed in any one of claims 1 to 4 wherein the ratio of the volume of the high sugar fraction to the volume of the low sugar fraction is from 50:50 to 60:40.
7. A method as claimed in claim 1 wherein volatile components are stripped from the high sugar fraction using a

spinning cone fractional distillation column.

8. A method as claimed in claim 7 wherein 1 to 15% of volatile component by volume of said high sugar fraction is stripped.

9. A method as claimed in any one of claims 1 to 8 wherein a skin fraction formed by extracting the pressed skin off the fruit with water or low sugar fraction is added to the finished wine.

10. A low alcohol wine when produced by any one of the methods as claimed in claims 1 to 9.

11. A method for the production of low alcohol wine substantially as hereinbefore described with reference to the accompanying drawings.

~~12. A process for separating a solute containing liquid into a high solute fraction and a low solute fraction, comprising cooling the liquid until at least a part of the liquid is frozen and forms particulate solids, passing the so frozen liquid into an inlet end of an extractor comprising a housing, which is upwardly inclined from its inlet end to an outlet end, and a helical screw conveyor disposed in the housing, rotating the helical screw conveyor and intermittently changing the direction of rotation of the screw conveyor while maintaining a net forward motion of the solids from the inlet end to the outlet end of the conveyor in a manner such that a solid low solute fraction is discharged from the outlet end of the extractor and a high solute fraction of unfrozen or melted liquid drains from the lower, inlet end of the extractor.~~

DATED this 25 day of September 1985

BIOQUIP AUSTRALIA PTY. LTD. and
COMMONWEALTH SCIENTIFIC AND
INDUSTRIAL RESEARCH ORGANIZATION

Patent Attorneys for the Applicant:






FIG. 2

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.